









CABLE LIST			UNIT CPU	UNIT DISC		
SIGNAL	COLOR	AWG	FROM		TO	
			CONN	PIN(S)	CONN	PIN(S)
			A	J		
SELECT LINE 2 ³	WHT/BRN/ORN WHT	26 88	CONT. #1	F 6	P2	Z
SELECT LINE 2 ²	WHT/BRN/YEL WHT			H 7		V
SELECT LINE 2 ¹	WHT/BRN/GRN WHT			J 8		R
SELECT LINE 2 ⁰	WHT/BRN/BLU WHT			K 9		L
SECTOR ADDR 2 ²	GRN WHT			L 10		KK
SECTOR ADDR 2 ¹	BLU WHT			M 11		JJ
TRACK ADDR 2 ⁵	VIO WHT			N 12		FF
TRACK ADDR 2 ⁴	GRY. WHT			P 13		X
TRACK ADDR 2 ⁷	BLK/WHT WHT			R 14		BB
TRACK ADDR 2 ⁶	BRN/WHT WHT			S 15		T
SECTOR ADDR 2 ⁰	RED/WHT WHT			T 16		CC
TRACK ADDR 2 ³	ORN/WHT WHT			U 17		J
TRACK ADDR 2 ¹	YEL/WHT WHT			V 18		N
TRACK ADDR 2 ⁰	GRN/WHT WHT			W 19		LL
TRACK ADDR 2 ²	BLU/WHT WHT			X 20		RR
HEAD SELECT	VIO/WHT WHT			Y 21		AA
READ DATA	ORN * WHT			E 5		C
WRITE DATA & CLOCK	RED * WHT			Z 22		B
READ CLOCK	RED * WHT		CONT. #1	A 1		
READ CLOCK	WHT RED		CONT. #2	A 1		
RD GATE	GRY/WHT WHT			2 B		E VV
RESTORE	WHT/BLK/BRN WHT			6 F		
WR GATE	WHT/BLK/RED WHT			7 H		EE
RDY TO S/W/R	WHT/BLK/ORN WHT			8 J		F
SEEK INCOMPLETE	WHT/BLK/YEL WHT			9 K		TT
LOG ADDR INTLK	WHT/BLK/GRN WHT	88	CONT. #2	L 10	P2	XX

(cont pg. 2)

LEGEND					NOTES: UNLESS OTHERWISE SPECIFIED						
DUAL SHIELDED - 		SHIELDED - 		TWISTED PAIR - 		* INDICATES SPECIAL 90Ω IMPEDANCE WIRE					
REV	PCO NO.	BY	DATE	APP	REV	PCO NO.	BY	DATE	APP	DRAWN L. Wilson DATE 9/0/71 CHECKED J. LYBERG DATE 9-17-71 ENGINEER MFG RELEASED 3-7-71	 FOUR-PHASE SYSTEMS, INC. CUPERTINO, CALIFORNIA CABLE LIST I/O CONTROLLER-DISC CABLE SIZE B 90014132-18 SHEET 1 OF 2 REV C
ADD. TOL. OF 3 IN. TO -05											
C PCO #4035 AW 12-15-78 JJ											
B PCO 1707 Van 7-9-71 JJ											
A3 PCO 0596 RKP 9-17-71 JJ											
A2 0576 AW 3-16-71 JJ											
A1 0255 AW 3-6-71 JJ											
A 0239 LW 10-23-71 JJ											
50 0197 JTC 8-17-71 JJ											

CABLE LIST			UNIT CPU	UNIT DISC		
SIGNAL	COLOR	AWG	FROM		TO	
			CONN	PIN(S)	CONN	PIN(S)
ADDR ACK	WHT/BLK/BLU WHT	26	CONT. #2	11 M	P2	NN
STROBE	WHT/BLK/VIO WHT			12 N		SS
SECTOR MARK	YEL * WHT			13 P		W
READ CLOCK	BRN * WHT	26	CONT. #2	1 A	P2	A
GROUND	BUSS	18			P2	D, WW

LEGEND		 DUAL SHIELDED =  SHIELDED =  TWISTED PAIR =		NOTES: UNLESS OTHERWISE SPECIFIED * INDICATES SPECIAL 90Ω IMPEDANCE WIRE.								
				DRAWN L. Wilson 9/9/71 CHECKED V. LYBERG 9-17-71 ENGINEER	 FOUR-PHASE SYSTEMS, INC. CUPERTINO, CALIFORNIA							
				MFG 9-17-71 RELEASED 3-7-72		CABLE LIST I/O CONTROLLER-DISC CABLE						
REV	PCO NO.	BY	DATE	APP	REV	PCO NO.	BY	DATE	APP	SIZE	90014132-18	C
										SHEET	2 OF 2	REV